




[Print this product](#)

Product Name	: Permanent Rubine (RPL)	Full Tone
Code No.	: 5704	
Chemical Class	: Monoazo Pigment	Tint Tone
Colour Index Name	: Pigment Red 57:1	
Colour Index No.	: 15850:1	
Basic Pigment C.A.S. No.	: 5281-04-9	

GENERAL DESCRIPTION :

Permanent Rubine RPL is a special quality Rubine Pigment having a very strong & economical bluish red pigment used in plastics application. Has very high dispersibility and excellent dielectric properties.

TECHNOLOGICAL CHARACTERISTICS :

Density	: 1.70 g/cm ³	Acid Resistance	: 5
Bulk Volume	: 3.5 L/Kg	Specific Surface	: 65 m ² /g
Alkali Fastness	: 3		

PROPERTIES :

	PE	PVC
Standard Depth (1/3g/kg)	1.45	4.75
Purity (°)	65.0	65.0
Light Fastness Mass Tone	6-7	6-7
Light Fastness Tint Tone	5	3-4
Heat Resistance (°C)	250	-
Weathering Fastness	-	-
Fastness to Bleeding	-	4-5

APPLICATIONS :

- Plasticized and Rigid PVC
- PVC
- LDPE
- HDPE

* This technical information is offered for guidance, but without guarantee.


[Print this product](#)
[^ Top](#)